

COMMERCIAL WASHER EXTRACTORS – Large range

Features

- Freestanding, high spin
- Stainless steel cabinet (AISI 304)
- Stainless steel drum and tub
- XControl Plus–fully programmable microprocessor
- Large door opening (diam. 54 cm) for easy loading and unloading
- Large drain valve (2×diam. 76 mm)
- Easy access to all parts
- Standard liquid soap connections
- Frequency controlled motor
- Patented soap dispenser with 5 removable compartments
- PowerWash® perforated lifting ribs: more mechanical action, lower water consumption
- Liquid manifold

Options

- Low steam pressure heating
- Liquid soap pumps
- SoftWash® version (wet cleaning)
- Trace-Tech® traceability software and networking system



	Lh335	Lh400	Lh550
Capacity	33 kg	40 kg	55 kg
Volume	335 l	400 l	518 l
Heating	EL., steam, hot water	EL, steam, hot water	EL., steam, hot water
Extraction	830 rpm	830 rpm	830 rpm
G – force	350	350	350
Electrical connection	1x220-240V 50/60 Hz 3x380-415V 50/60 Hz	1x220-240V 50/60 Hz 3x380-415V 50/60 Hz	1x220-240V 50/60 Hz 3x380-415V 50/60 Hz
Electrical heating	24 kW	36 kW	54 kW
Door diameter	540 mm	540 mm	540 mm
Dimensions H x W x D (mm)	1905 x 1195 x 1330	1905 x 1195 x 1430	1905 x 1195 x 1610

	Lh800	Lh1000	Lh1250
Capacity	80 kg	100 kg	120 kg
Volume	807 l	1003 l	1180 l
Heating	EL., steam, hot water	steam, hot water	steam, hot water
Extraction	750 rpm	720 rpm	695 rpm
G – force	350	350	350
Electrical connection	1x220-240V 50/60 Hz 3x380-415V 50/60 Hz	1x220-240V 50/60 Hz 3x380-415V 50/60 Hz	1x220-240V 50/60 Hz 3x380-415V 50/60 Hz
Electrical heating	67,5 kW	-	-
Door diameter	530 mm	530 mm	650 mm
Dimensions HxWxD (mm)	1985 x 1495 x 1940	2060 x 1790 x 2005	2085 x 1855 x 2085