

Features

- Large capacity-Stainless steel top panel & Anthracite grey front and side panels
- Patented soap hopper
- New perforation of inner drum (Cascade)
- Large drain valve (Ø 76 mm)
- Frequency controlled motor
- Easy access to all vital parts from the front
- Large door opening for easy loading & unloading

Options

- X Control Plus - Fully programmable
- Coin operated timer (CPS)
- USB plug (on the back panel)
- Stainless steel front and side panels
- Easy soap - Liquid soaps connection
- Liquid soap pumps
- Water recovery kit
- Steam heating version



	Af80	Af105	Af135
Capacity	8 kg	11 kg	14 kg
Volume	75 l	105 l	135 l
Heating	EL., steam, hot water	EL, steam, hot water	EL., steam, hot water
Extraction	1165 rpm	1075 rpm	1075 rpm
G – force	400	400	400
Electrical connection	1x220-240V 50/60 Hz 3x380-415V 50/60 Hz	1x220-240V 50/60 Hz 3x380-415V 50/60 Hz	1x220-240V 50/60 Hz 3x380-415V 50/60 Hz
Electrical heating	6 kW	9 kW	12 kW
Door diameter	330 mm	410 mm	410 mm
Dimensions H x W x D (mm)	1115 x 710 x 790	1225 x 795 x 795	1225x795x945

	Af180	Af240	Af280
Capacity	18 kg	24 kg	28 kg
Volume	180 l	240 l	280 l
Heating	EL., steam, hot water	EL., steam, hot water	EL., steam, hot water
Extraction	980 rpm	980 rpm	915 rpm
G – force	400	400	350
Electrical connection	1x220-240V 50/60 Hz 3x380-415V 50/60 Hz	1x220-240V 50/60 Hz 3x380-415V 50/60 Hz	1x220-240V 50/60 Hz 3x380-415V 50/60 Hz
Electrical heating	18 kW	18 kW	22 kW
Door diameter	460 mm	460 mm	460 mm
Dimensions HxWxD (mm)	1410x970x970	1410x970x1105	1410x970x1185