



Features

- Large surface contact with linen over an angle of 300°
- Finger protection and emergency button for more safety
- Durable NOMEX ironing belts
- Automatic cooldown
- Easy to operate microprocessor
- Indication of ironing speed and temperature
- Frequency controlled motor
- Space saving installation against the wall is possible:
front return

Options

- Coin operated version
- Chrome-plated cylinder for better thermal conduction and ironing quality
- Overheating check system (OCS) with 3 temperature sensors
- Pedal of insert table stop system

	LSR 3316	LSR 3320
Roller diameter	320 mm	320 mm
Roller length	1664 mm	2080 mm
Roller speed	1 – 6 m/min	1 – 6 m/min
output	58 kg/h	72 kg/h
Heating	Electrical, gas	Electrical, gas
Electrical connection	3 x 240V 50/60 Hz 3 x 380-415V+N 50/60 Hz	3 x 240V 50/60 Hz 3 x 380-415V+N 50/60 Hz
Electrical heating	24,3 kW	27,9 kW
Net weight	435 kg	490 kg
Dimensions H x W x D (mm)	1110 x 2084 x 755	1110 x 2500 x 755

	LSR 5016	LSR 5020	LSR 5025	LSR 5032
Roller diameter	500 mm	500 mm	500 mm	500 mm
Roller length	1600 mm	2000 mm	2500 mm	3200 mm
Roller speed	1,5 – 8 m/min	1,5 – 8 m/min	1,5 – 8 m/min	1,5 – 8 m/min
output	65 kg/h	80 kg/h	95 kg/h	120 kg/h
Heating	El., gas, steam	El., gas, steam	El., gas, steam	El., gas, steam
Electrical connection	3 x 240V 50/60 Hz 3 x 380-415V+N	3 x 240V 50/60 Hz 3 x 380-415V+N	3 x 240V 50/60 Hz 3 x 380-415V+N	3 x 240V 50/60 Hz 3 x 380-415V+N
Electrical heating	33 kW	38 kW	55 kW	65 kW
Net weight	920 kg	1150 kg	1290 kg	1590 kg
Dimensions H x W x D (mm)	1232 x 2350 x 992	1232 x 2750 x 992	1232 x 3350 x 992	1232 x 3950 x 992