

7 INDUSTRIAL CYLINDER HEATED DRYING IRONERS WITH OPTIONS



Features

- Large surface contact with linen over an angle of 300°
- Safety finger protection and emergency button for more safety
- Durable NOMEX ironing belts
- Automatic cooldown
- Easy to operate microprocessor: 20 pre-set ironing programs
- Indication of ironing speed and temperature
- Reverse mode possible
- Variable setups for folding
- LSRP model: integrated length folder model
- LSRA model: rear return
- Frequency controlled motor
- Easy to remove lint filters
- Standard anti-static bar
- Easyfold® system requires less maintenance (no ribbons and rolls)
- Electric, gas or steam heating on most models

Options

- Foot pedal for easy start and stop
- Front return (LSRP)
- Output table (LSRP)
- Chrome-plated cylinder for a better thermal conduction
- LSREP model with cross folder and stacker

	Integrated feeding system	Integrated length folder	Linen return
LSRA model	N/A	N/A	Rear/Front
LSRP model	N/A	standard	Front
LSREP model	standard	standard	Rear/Front

	LSRP 5020 / LSRA 5020	LSRP 5025 / LSRA 5025	LSRP 5032 / LSRA 5032
Roller diameter	500 mm	500 mm	500 mm
Roller length	2000 mm	2500 mm	3200 mm
Roller speed	1,5 – 8 m/min	1,5 – 8 m/min	1,5 – 8 m/min
output	80 kg/h	95 kg/h	120 kg/h
Heating	El., gas, steam	El., gas, steam	El., gas, steam
Electrical connection	3 x 240V 50/60 Hz 3 x 380-415V+N 50-60 Hz	3 x 240V 50/60 Hz 3 x 380-415V+N 50-60 Hz	3 x 240V 50/60 Hz 3 x 380-415V+N 50-60 Hz
Electrical heating	38 kW	55 kW	65 kW
Net weight	1290 kg	1440 kg	1680 kg
Dimensions H x W x D (mm)	1568 x 2750 x 1185	1568 x 3350 x 1185	1568x3950x1185

	LSREP 5020	LSREP 5025	LSREP 5032
Roller diameter	500 mm	500 mm	500 mm
Roller length	2000 mm	2500 mm	3200 mm
Roller speed	1,5 – 8 m/min	1,5 – 8 m/min	1,5 – 8 m/min
output	80 kg/h	95 kg/h	120 kg/h
Heating	El., gas, steam	El., gas, steam	gas, steam
Electrical connection	3 x 240V 50/60 Hz 3 x 380-415V+N 50-60 Hz	3 x 240V 50/60 Hz 3 x 380-415V+N 50-60 Hz	3 x 240V 50/60 Hz 3 x 380-415V+N 50-60 Hz
Electrical heating	38 kW	55 kW	65 kW
Net weight	1720 kg	2180 kg	2400 kg
Dimensions H x W x D (mm)	request	request	request