

Features

- AIR RE-CYCLE recirculation system that reintroduces the expelled hot air inside the drum
- SMART DRY, new intelligent humidity sensor
- Stainless steel drum
- Electronic microprocessor
- FIRE EXTINGUISHER, Integrated fire extinguishing system
- Thermally insulated panels
- Double door glass for greater energy savings
- Full airflow, complemented axial-radial airflow with further openings
- Reverse drum
- Stamped drum perforation for gentle dry

Options

- Panels in stainless steel



	GL 210	GL 330	GL 460	GL 550
Capacity (1:20)	11 kg	17	23	27
Volume	210 l	330 l	460 l	550 l
Drum diameter	750 mm	750 mm	855 mm	947 mm
Drum length	475 mm	746 mm	800 mm	780 mm
Door diameter	574 mm	574 mm	574 mm	802 mm
Heating	El., steam, gas	El., steam, gas	El., steam, gas	El., steam, gas
Electrical connection	400V 3ph , 230V 3 ph	400V 3ph, 230V 3 ph	400V 3ph, 230V 3 ph	400V 3ph, 230V 3 ph
Electrical heating	12 kW	18 kW	24 kW	30 kW
Max airflow	1200 m3/h	1200 m3/h	1500 m3/h	1500 m3/h
Dimensions H x W x D (mm)	1694 x 785 x 840	1694 x 785 x 1100	1812 x 890 x 1245	1946 x 985 x 1054

	GL 660	GL 900	GL 1200	GL 1500
Capacity (1:20)	33	45	60	75
Volume	660 l	896 l	1202 l	1500 l
Drum diameter	947 mm	1225 mm	1225 mm	1225 mm
Drum length	936 mm	760 mm	1020 mm	1252 mm
Door diameter	802 mm	802 mm	802 mm	802 mm
Heating	El., steam, gas	El., steam, gas	El., steam, gas	El., steam, gas
Electrical connection	400V 3ph, 230V 3 ph	400V 3ph, 230V 3 ph	400V 3ph, 230V 3 ph	400V 3ph, 230V 3 ph
Electrical heating	36 kW	54 kW	72 kW	72 kW
Max airflow	1500 m3/h	4500 m3/h	4500 m3/h	4500 m3/h
Dimensions H x W x D (mm)	1946 x 985 x 1210	2380 x 1270 x 1085	2380 x 1270 x 1345	2380 x 1270 x 1577